SAFETY DATA SHEET

TYGRIS

SOLVENT TOOL & ELECTRONICS CLEANER

SECTION 1: Identification of the substance/mixture and of the company/undertaking **1.1 Product identifier** Trade name: SOLVENT TOOL & ELECTRONICS CLEANER Article number: **IS2** 1.2 Relevant identified uses of the substance or mixture and uses advised against **Product category:** Solvent cleaner 1.3 Details of the supplier of the safety data sheet **TYGRIS** Industrial Manufacturer/Supplier: Unit 31, Kyle Road Industrial Estate Irvine Ayrshire KA12 8LE Tel +44 (0) 1294 311 066 Email technical@tygrisindustrial.com **Further information Technical Department** obtainable from: 1.4 Emergency telephone Tel +44 (0) 1294 311 066 number: **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture **Physical hazards:** Aerosol 1 - H222 Health hazards: Eye Irrit. 2 - H319, STOT SE 3 - H336 2.2. Label elements H222: Extremely flammable aerosol. Hazard statements: H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. GHS02: Flame Hazard pictograms: GHS07: Exclamation mark Signal word: Danger **Precautionary statements:** P102: Keep out of reach of children. P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P211: Do not spray on an open flame or other ignition source. P251: Pressurized container: Do not pierce or burn, even after use. P261: Avoid breathing vapour/spray. P271: Use only outdoors or in a well-ventilated area. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical advice/attention. P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Supplementary P501: Dispose of contents/container in accordance with local regulations. precautionary statements: P264: Wash contaminated skin thoroughly after handling. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P403+233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Supplemental label information: H229: Pressurised container: May burst if heated

2.3. Other hazards



SAFETY DATA SHEET SOLVENT TOOL & ELECTRONICS CLEANER

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PROPAN-2-OL

| EC | CAS | Index number | CLP Classification | Percent |
|-----------|---------|--------------|--|---------|
| 200-661-7 | 67-63-0 | - | Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 | 60-100% |

BUTANE

| 203-448-7 | 106-97-8 | - | Flam. Gas 1 - H220 | 5-10% |
|-----------|----------|---|--------------------|-------|
| ISOBUTANE | | | | |
| 200-857-2 | 75-28-5 | - | Flam. Gas 1 - H220 | 1-5% |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| General information: | Move the exposed person to fresh air at once. Get medical attention if any discomfort continues. |
|----------------------|--|
| Skin contact: | Wash the skin immediately with soap and water. Get medical attention if any discomfort continues. |
| Eye contact: | Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues. |
| Ingestion: | DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues. |
| Inhalation: | Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention. |

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

| SECTION 5: Firefighting measures | | |
|--|---|--|
| 5.1 Extinguishing media | | |
| Extinguishing media: | Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist. | |
| 5.2. Special hazards arising from the substance or mixture | | |
| Exposure hazards: | Aerosol cans may explode in a fire. | |
| 5.3. Advice for fire-fighters | | |
| Special fire fighting procedures: | Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. | |



SAFETY DATA SHEET SOLVENT TOOL & ELECTRONICS CLEANER

IS2

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

| SECTION 7: Handling and storage | | |
|---|--|--|
| 7.1 Precautions for safe handling | | |
| Handling requirements: | Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. | |
| 7.2. Conditions for safe storage, including any incompatibilities | | |
| Storage conditions: | Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. | |
| 7.3. Specific end use(s) | | |
| SECTION 8: Exposure controls/personal protection | | |

8.1. Control parameters

Workplace exposure limits:

BUTANE

| Long-term exposure limit (8-hour TWA) | Short-term exposure limit (15-minute) |
|---------------------------------------|---------------------------------------|
| WEL 600 ppm, 1450 mg/m ³ | WEL 750 ppm, 1810 mg/m ³ |

PROPAN-2-OL

| PROPAN-2-OL | | |
|--|--|---|
| WEL 400 ppm, 999 mg/m ³ | | WEL 500 ppm, 1250 mg/m ³ |
| WEL = Workplace Exposure Limits 8.2. Exposure controls | | |
| Protective equipment: | | |
| Engineering measures: | Provide adequate general a | and local exhaust ventilation. |
| General protective and hygienic measures: | | AREA! Wash hands at the end of each work shift and before the toilet. Promptly remove any clothing that becomes do not eat, drink or smoke. |
| Respiratory protection: | | on made, but respiratory protection must be used if the general nended occupational exposure limit. Use chemical cartridge cartridge. |
| Hand protection: | Use protective gloves. | |
| Eye protection: | Use approved safety goggle | es or face shield. |
| Other Protection: | Wear appropriate clothing t prolonged vapour contact. | o prevent any possibility of liquid contact and repeated or |



SAFETY DATA SHEET

SOLVENT TOOL & ELECTRONICS CLEANER IS2

| SECTION 9: Physical and che | emical properties | |
|--|--|--|
| 9.1. Information on basic physical and chemical properties | | |
| State: | Aerosol | |
| Colour: | Colourless. | |
| Odour: | Characteristic | |
| Solubility: | Slightly soluble in water | |
| Flammability limits: | Lower: 0.8 % Upper: 12.0 % | |
| 9.2. Other information | | |
| SECTION 10: Stability and rea | activity | |
| 10.1. Reactivity | | |
| 10.2. Chemical stability | | |
| Chemical stability: | Stable under normal temperature conditions. | |
| 10.3. Possibility of hazardous | s reactions | |
| 10.4. Conditions to avoid | | |
| Conditions to avoid: | Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids. | |
| 10.5. Incompatible materials | | |
| 10.6. Hazardous decompositi | on products | |
| Fire creates: | Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). | |
| SECTION 11: Toxicological information | | |
| 11.1. Information on toxicolog | gical effects | |
| Skin contact: | Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin. | |
| Eye contact: | Irritating to eyes. May cause chemical eye burns. | |
| Inhalation: | May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. | |
| Ingestion: | May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. | |
| Route of entry: | Inhalation. Skin and/or eye contact. | |
| SECTION 12: Ecological Infor | SECTION 12: Ecological Information | |
| 12.1. Toxicity | | |
| Ecotoxicity: | Dangerous for the environment if discharged into watercourses. | |
| 12.2. Persistence and degradability | | |
| 12.3 Rioaccumulative notential | | |

- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects



31 Kyle Road, Irvine KA12 8LE Tel: +44 (0) 1294 311 066 technical@tygrisindustrial.com

Compilation Date: 16/09/2021 Version 2 Page 4 of 6

SAFETY DATA SHEET

SOLVENT TOOL & ELECTRONICS CLEANER

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

General information:

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

| SECTION 14: Transport Information | | |
|-----------------------------------|-------------------|--|
| UN Number (ADR): | 1950 | |
| UN Number (IMDG): | 1950 | |
| UN Number (IATA): | 1950 | |
| 14.2 UN proper shipping name | | |
| Proper shipping name: | AEROSOLS | |
| 14.3. Transport hazard class(e | s) | |
| ADR/RID/ADN Class: | 2, Class 2: Gases | |
| ADR Label No. IMDG | 2.1 | |
| Class: | 2.1 | |
| ICAO Class/Division: | 2.1 | |
| Transport labels: | | |
| 14.4. Packing group | | |
| Packing group: | Not applicable. | |
| 14.5 Environmental hazards | | |
| Marine pollutant: | No | |
| 14.6 Special precautions for us | Ser | |
| EmS: | 2-13 | |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory Information

| 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture | | |
|--|---|--|
| Statutory Instruments: | The Aerosol Dispensers (Amendment) Regulations 2014 No.1130. | |
| Guidance Notes: | Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. | |
| EU Legislation: | The Aerosol Dispensers Directive 1975/324 EEC. Regulation (EC) No.1272/2008: The Classification, Labelling and Packaging of substances and mixtures Regulations. Regulation (EC) No. 1907/2006: The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH). 2001/95/EC The General Product Safety Directive (GPSD). Commission Regulation (EU) 2015/830: Requirements for the compilation of safety data sheets (amending REACH). Authorisations (Title VII Regulation 1907/2006): No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006): No specific restrictions of use are noted for this product. | |

15.2. Safety, health and environmental regulations/legislation specific for the substance or mixture





SAFETY DATA SHEET SOLVENT TOOL & ELECTRONICS CLEANER

IS2

SECTION 16: Other Information

| Other information: | This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830. |
|------------------------------|--|
| Phrases used in s.2 and s.3: | H220: Extremely flammable gas. H222: Extremely flammable aerosol. H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. |
| Legal disclaimer | The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. |

