

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: CLEAR ACRYLIC LACQUER

Article number: R242

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category: Paint aerosol

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial
Unit 31, Kyle Road Industrial Estate
Irvine
Ayrshire
KA12 8LE
Tel +44 (0) 1294 311 066
Email technical@tygrisindustrial.com

Further information obtainable from: Technical Department

1.4 Emergency telephone number: Tel +44 (0) 1294 311 066

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Physical hazards: Aerosol 1 - H222
Health hazards: EUH066, Eye Irrit. 2 - H319, STOT SE 3 - H336

2.2. Label elements

Hazard statements: H222: Extremely flammable aerosol.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark



Signal word: Danger

Precautionary statements: P102: Keep out of reach of children.
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P211: Do not spray on an open flame or other ignition source.
P251: Pressurized container: Do not pierce or burn, even after use.
P261: Avoid breathing vapour/spray.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical advice/attention.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50° C/122°F.
P501: Dispose of contents/container in accordance with local regulations.

Supplementary precautionary statements: P264: Wash contaminated skin thoroughly after handling.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P403+233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Supplemental label information: EUH066: Repeated exposure may cause skin dryness or cracking.
H229: Pressurised container: May burst if heated

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EC	CAS	Index number	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 EUH066	30-60%

BUTANE

203-448-7	106-97-8	-	Flam. Gas 1 - H220	5-10%
-----------	----------	---	--------------------	-------

2-BUTOXYETHANOL

203-905-0	111-76-2	-	Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	5-10%
-----------	----------	---	--	-------

2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	-	Flam. Liq. 3 - H226	1-5%
-----------	----------	---	---------------------	------

ISOBUTANE

200-857-2	75-28-5	-	Flam. Gas 1 - H220	1-5%
-----------	---------	---	--------------------	------

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
Skin contact:	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
Eye contact:	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Ingestion:	DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.
Inhalation:	Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information:	The severity of the symptoms described will vary dependant of the concentration and the length of exposure.
Skin contact:	Prolonged skin contact may cause redness and irritation.
Eye contact:	Irritating and may cause redness and pain.
Ingestion: Inhalation:	Due to the physical nature of this material it is unlikely that swallowing will occur. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media:	Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
-----------------------------	--

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:	When heated, vapours/gases hazardous to health may be formed.
Unusual fire & explosion hazards:	Aerosol cans may explode in a fire.
Specific hazards:	Aerosol containers can explode when heated, due to excessive pressure build-up.

5.3. Advice for fire-fighters

Special fire fighting procedures:	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
Protective equipment for fire-fighters:	Wear full protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions, protective equipment and emergency procedures:

Follow precautions for safe handling described in this safety data sheet. Wear protective gloves. Do not smoke, use open fire or other sources of ignition. Avoid inhalation of vapours and aerosol spray. Avoid contact with skin and eyes.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Clean-up procedures:

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Reference to other sections: For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handling requirements:

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Store in a cool and well-ventilated place. Store in accordance with the advice of insurers and/or relevant authority. Store in a dry, well ventilated, moisture free area.

7.3. Specific end use(s)

Usage description:

Decorative paint coating for a range of substrates. Aerosolised paint spray.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA)	Short-term exposure limit (15-minute)
WEL 25 ppm (Sk)	WEL 50 ppm (Sk)

ACETONE

WEL 500 ppm, 1210 mg/m ³	WEL 1500 ppm, 3620 mg/m ³
-------------------------------------	--------------------------------------

BUTANE

WEL 600 ppm, 1450 mg/m ³	WEL 750 ppm, 1810 mg/m ³
-------------------------------------	-------------------------------------

2-METHOXY-1-METHYLETHYL ACETATE

WEL 50 ppm, 274 mg/m ³	WEL 100 ppm, 548 mg/m ³
-----------------------------------	------------------------------------

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment:



Engineering measures:

Provide adequate general and local exhaust ventilation.

General protective and hygienic measures:

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection:

Filter apparatus, type AX (EN371).

Hand protection:

Suitable gloves.

Eye protection:

Use approved safety goggles or face shield.

Other Protection:

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol
Colour:	Colourless
Odour:	Ketonic. Characteristic of a solvent based paint product
Solubility:	Insoluble in water
Flammability limits:	Lower: 0.8 % Upper: 9.0 %

9.2. Other information

Volatile Organic Compound (VOC):	Maximum 839 g/litre. Aerosol products which are used for vehicle refinishing are classed as Annex II B subcategory (e). The maximum permitted VOC's are 840 g/l. The typical VOC content for this range of products is between 625 and 675 g/l. The VOC regulations do not apply to any other aerosol products except those which are used for vehicle refinishing.
---	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	The product may form explosive vapours/air mixtures even at normal room temperatures
-------------------	--

10.2. Chemical stability

Chemical stability:	Stable under normal temperature conditions.
----------------------------	---

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid:	Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids. Avoid exposing aerosol containers to high temperatures or direct sunlight.
-----------------------------	---

10.5. Incompatible materials

Materials to avoid:	Strong acids. Strong alkalis. Strong oxidising substances.
----------------------------	--

10.6. Hazardous decomposition products

Fire creates:	Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂).
----------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin contact:	Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.
Eye contact:	Irritating to eyes. May cause chemical eye burns.
Inhalation:	May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion:	May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.
Route of entry:	Inhalation. Skin and/or eye contact.

SECTION 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

Degradability: The majority of the constituents are readily degradable.

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility: The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information: Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. Industrial and institutional users should dispose of aerosols through a registered waste disposal company.

SECTION 14: Transport information

UN Number (ADR): 1950

UN Number (IMDG): 1950

UN Number (IATA): 1950

14.2 UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

ADR/RID/ADN Class: 2, Class 2: Gases

ADR Label No. 2.1

IMDG Class: 2.1

ICAO Class/Division: 2.1

Transport labels:



14.4. Packing group

Packing group: Not applicable.

14.5 Environmental hazards

Marine pollutant: No

14.6 Special precautions for user

EmS: F-D, S-U

Tunnel restriction code: (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments:	The Aerosol Dispensers (Amendment) Regulations 2014 No.1130.
Guidance Notes:	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.
EU Legislation:	The Aerosol Dispensers Directive 1975/324 EEC. Regulation (EC) No.1272/2008: The Classification, Labelling and Packaging of substances and mixtures Regulations. Regulation (EC) No. 1907/2006: The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH). 2001/95/EC The General Product Safety Directive (GPSD). Commission Regulation (EU) 2015/830: Requirements for the compilation of safety data sheets (amending REACH). Authorisations (Title VII Regulation 1907/2006): No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006): No specific restrictions of use are noted for this product.

15.2. Safety, health and environmental regulations/legislation specific for the substance or mixture

SECTION 16: Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking. H220: Extremely flammable gas. H222: Extremely flammable aerosol. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H302: Harmful if swallowed. H312: Harmful in contact with skin. H315: Causes skin irritation. H319: Causes serious eye irritation. H332: Harmful if inhaled. H336: May cause drowsiness or dizziness.
Legal disclaimer	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.