



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SEIZE RELEASE PENETRATING OIL

Article number: R275

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC24: Lubricants, greases, release products.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial

Unit 31

Kyle Road Industrial Estate

Irvine Ayshire KA12 8LE

Tel +44 (0) 1294 311 066

Email technical@tygrisindustrial.com

Further information obtainable from:

obtainable from: Technical Department

1.4 Emergency telephone

number: Tel +44 (0) 1294 311 066





#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Aerosol 1: H222; -:

H229

Most important adverse

effects:

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting

effects.

2.2. Label elements

**Hazard statements:** H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal word:

Danger

**Precautionary statements:** P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P410

+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.



## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## Hazardous ingredients:

#### PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%

## ACETONE - REACH registered number(s): 01-2119471330-XXXX

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	1-10%	
			STOT SE 3: H336; -: EUH066		

HYDROCARBONS, C9-12, N-ALKANES, ISOALKANES, CYCLICS, (2-25%) AROMATICS - REACH registered number(s): 01-2119458049-33

919-446-0	-	-	Flam. Liq. 3: H226; STOT SE 3: H336;	
			Asp. Tox. 1: H304; Aquatic Chronic 2:	
			H411; -: EUH066	

#### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor. Move the exposed person to fresh air.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely. There may be

**Ingestion:** soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special

treatment:

Eye bathing equipment should be available on the premises.







## **SECTION 5: Firefighting measures**

5.1 Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to

cool containers.

5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

## **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking

containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## **SECTION 7: Handling and storage**

7.1 Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.



## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

**Hazardous ingredients:** 

PROPAN-2-OL

Workplace exposure limits:

## Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m³	1250 mg/m³	-	-

## **ACETONE**

UK	500ppm 1210mg/m <sup>3</sup>	1500ppm 3620mg/m <sup>3</sup>	-	-

## **DNEL/PNEC Values**

## Hazardous ingredients:

#### **ACETONE**

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	186mg/kg/day	Workers	Systemic
DNEL	Inhalation	2420mg/m3	Workers	Local
DNEL	Inhalation	1210mg/m3	Workers	Systemic
DNEL	Oral	62mg/kg/day	Consumers	Systemic
DNEL	Dermal	62mg/m3	Consumers	Systemic
DNEL	Inhalation	200mg/m3	Consumers	Systemic
PNEC	Fresh water	10.6mg/l	-	-
PNEC	Marine water	1.06mg/l	-	-
PNEC	Fresh water	Intermittent release	-	-
PNEC	Fresh water sediments	30.4 mg/kg	-	-
PNEC	Marine sediments	3.04mg/kg	-	-
PNEC	Soil (agricultural)	29.5mg/kg	-	-
PNEC	Microorganisms in sewage treatment	100mg/l	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory equipment:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves. Chemically resistant gloves. **Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection:Protective clothing.Environmental:Not applicable.







## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Yellow-brown

Odour: Characteristic odour

Solubility in water: Insoluble

Also soluble in: Most organic solvents

Flash point°C: -60
Relative density: 0.83

9.2. Other information

Other information: No data available.

## **SECTION 10: Stability and reactivity**

10.1. Reactivity Reactivity:

**10.2. Chemical stability** Stable under recommended transport or storage conditions.

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.





## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

## **Hazardous ingredients:**

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

## **ACETONE**

DERMAL	RAT	LD50	>7400	mg/kg
DERMAL	RBT	LD50	2000	mg/kg
ORAL	RAT	LD50	5800	mg/kg
VAPOURS	RAT	4H LC50	76000	mg/l

## Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

Other information: Not applicable.





## **SECTION 12: Ecological information**

## 12.1. Toxicity

## **Hazardous ingredients:**

**ACETONE** 

ALGAE	192H EC10	530	mg/l
Activated Sludge	30m EC10	1000	mg/l
DAPHNIA	48H EC50	8800	mg/l
Daphnia magna	192H EC10	2212	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	5540	mg/l

## 12.2. Persistence and degradability

Persistence and degradability:

Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential:

No bioaccumulation potential.

12.4. Mobility in soil

Mobility:

Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification:

This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects:

Negligible ecotoxicity.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Disposal operations:

Transfer to a suitable container and arrange for collection by specialised disposal company. Dispose of contents and container according to national regulations.

Not applicable. **Recovery operations:** Disposal of packaging: Not applicable.

NB:

The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Version 2

Page 8 of 9

## **SAFETY DATA SHEET**



## SEIZE RELEASE PENETRATING OIL R275

## **SECTION 14: Transport information**

14.1. UN number

**UN** number: UN1950

14.2. UN proper shipping name

Shipping name: **AEROSOLS** 

14.3. Transport hazard class(es) 2

Transport class:

14.4. Packing group

14.5. Environmental hazards

**Environmentally hazardous:** No Marine pollutant: No 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D **Transport category:** 2

## **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical safety assessment

Chemical safety A chemical safety assessment has not been carried out for the substance or the mixture

assessment: by the supplier.

## **SECTION 16: Other information**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated. H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.

The above information is believed to be correct but does not purport to be all inclusive and Legal disclaimer:

shall be used only as a guide. This company shall not be held liable for any damage

resulting from handling or from contact with the above product.

