



Description

PROTEAN Multi-Lube is a NSF: H1 registered general purpose food grade lubricant for use on cables, chains, castors, hinges, bearings and pins.

Suitable for use within Food & Beverage, Packaging, Pharmaceutical and other cleanroom environments.

Outstanding Features

- NSF: H1 registered
- Effective over a wide temperature range
- Good water displacement and penetration properties
- Effective corrosion resistance
- Temperature range: -20°C to +200°C
- 360° valve for inverted use

Directions for Use

- Store out of direct sunlight and below +50°C
- Consult the safety data sheet prior to use
- Shake aerosol well before use
- Once sprayed, allow the lubricant to thicken on before use
- Use the extension tube for greater accuracy.
- Do not spray directly onto food

Technical Data

Category	H1 registered (lubricant with incidental food contact, for use in and around food processing areas)
NSF Certificate No.	139271 Does not contain any genetically modified ingredients, nut oils or animal derivatives
Appearance	Off-white, light viscosity oil
Odour	Vegetable oil, barely perceptible
Contents	Blend of oils, propan-2-ol and propane / butane / isobutane propellant
Flammability	Extremely flammable
Storage	Below 50°C
Flash Point	>100°C
Temperature range	-20° to 200°C
Relative Density	0.89
Solubility	Insoluble in water
Pack Sizes	12 x 400ml cans

The content of this data sheet is given in good faith but without warranty.