TECHNICAL DATA SHEET

PROTEAN PROPASTE
F405

Description

PROTEAN ProPaste is a NSF: H1 registered, spray-formulated, tenacious lubricant suitable for use within Food & Beverage, Packaging, Pharmaceutical and other cleanroom environments.

Engineered as an anti-seize paste, PROTEAN ProPaste is ideal for the assembly and lubrication of bushes, slides, threads and small open gears and also suitable as a food grade drilling, cutting and tapping lubricant in areas where in-situ repair and maintenance is required.

Benefits & Features

- NSF: H1 registered
- Highly versatile tenacious lubricant, resists water wash off
- Innovative anti-seize paste for assembly and lubrication
- Suitable for use as a food grade metal working paste
- Ideal for use on stainless steel fasteners
- 360Ávalve for inverted use

Directions for Use

- Store out of direct sunlight and below +50ęC
- Consult the safety data sheet prior to use
- Shake aerosol well before use, and use in a well ventiliated environment
- For best results, ensure components to be sprayed are clean and free of dirt, grime and water
- Spray both male and female parts and remove any excess ProPaste after fitting
- Do not spray directly onto food

Technical Data

Category:	H1 registered (lubricant with incidental food contact, for use in and around food processing areas)
NSF Certificate No:	154797
Allergens:	Does not contain any genetically modified ingredients, nut oils or animal derivatives
Appearance:	A white paste
Odour:	Barely perceptible
Contents:	Blend of white mineral oil and propane / butane / isobutane propellant
Flammability:	Extremely flammable aerosol
Storage:	Below 50˚C
Flash Point:	-60˚C
Relative Density:	0.91
Solubility:	Insoluble in water
Temperature Range:	-20 to 150°C
Pack Sizes:	12 x 400ml cans

The content of this data sheet is given in good faith but without warranty.