



Description

PROTEAN food safe performance lubricant for ejector pins, pillars and bushes

F445 is a high temperature, food area safe synthetic product suitable for the lubrication of ejector pins, pillars and bushes fitted to plastic injection moulding machines. Refined and highly tenacious, it is used where a higher mould temperature is reached and will not cause contamination to mouldings, helping to prevent seizure and to protect against corrosion.

Outstanding Features

- H1 registered for use in food environments
- Highly tenacious – resistant to leakage
- Provides long lasting lubrication
- No mould contamination
- High surface slip
- Suitable up to 240°C
- Water resistant
- Fully synthetic

Directions for Use

Shake can well before use and apply sparingly from a distance of 20 to 30 cm. Wipe off excess with a clean cloth. Use applicator straw for difficult to reach areas.

Technical Data

Category	H1 – Lubricants with incidental contact
NSF Certificate No	122839
	Does not contain genetically modified ingredients, nut oils or animal derivatives
Appearance	Clear liquid
Odour	Virtually odourless
Contents	Blend of synthetic oils and butane/ propane propellant
Storage	Below 50°C
Flash Point	<0°C
Temperature range	-20° to 240°C
Relative Density	0.88
Solubility	Insoluble in water
Pack Sizes	12 x 400ml cans

Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.