

#### Description

Premium quality paints. Acrylic-based top-coat paints and for a professional finish on most substrates with exceptional ease of use, resulting in a high quality appearance, with Vari-Spray nozzles for superb controllability.

#### Benefits & Features

- Acrylic formulation for greater flexibility
- Gives excellent adhesion
- Compatible with most materials
- Can be applied over previously painted surfaces
- Wear and scratch resistant
- High opacity
- Lead Free
- Excellent UV stability – non-fading, lasting gloss
- Vari-Spray nozzles for differing spray patterns
- Integral coloured caps for easy identification
- Any RAL or BS colour available to order
- Two mixing balls for fast start up

#### Directions for Use

Ensure surface is clean, dry and free from grease. For uneven surfaces, those requiring a complete colour change or extra protection, apply primer first. Prepare with a light sanding for good adhesion. Adjust nozzle for desired spray pattern. Shake can vigorously for 2 minutes and spray a number of light coats with a sweeping action from 25-30cm. Paint should be touch-dry and ready for over-coating in 15 minutes and fully dry within 24 hours. After use, invert can and spray to clear nozzle. Coverage 1.5-2m<sup>2</sup> per can.

#### Technical Data

Appearance:	Gloss Dark Green
Odour:	Typical paint aroma
Contents:	Blend of pigments, viscosity modifiers, stabilisers, solvents and hydrocarbon propellants
Flash Point:	<0°C
Solubility:	
Temperature Range:	Maximum temperature in use 110°C
Relative Gravity:	0.797
VOC Content:	91% approx
Solids Content:	9% approx
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at <a href="http://tygrisindustrial.com">tygrisindustrial.com</a> )
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols

#### Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

