

Description

Solvent based weld anti-spatter release spray. A special non-silicone formulation ideal for use on all types of welding equipment to prevent the adhesion of welding spatter. It can be applied to workpieces, nozzles, shrouds, jigs and tools and enables free gas flow in inert gas welding.

Benefits & Features

- Non-chlorinated
- Non-silicone – can be used with products that require finishing
- Rapid drying
- Prevents adhesion – spatter easily removed
- Non flammable
- Colourless – non-staining
- Does not gum up when subject to heat

Directions for Use

Shake can well before use. Hold can upright and spray a thin, just visible, even film from a distance of 30cm. Normal industrial degreasing methods will remove any residual film if necessary.

Technical Data

Appearance:	Pale yellow clear liquid
Odour:	Slight vegetable oil
Contents:	Blend of refined vegetable oils in a petroleum naphtha with butane, isobutane and propane propellant
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	Designed for use at ambient temperatures
Relative Density:	1.198
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 300ml aerosols

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

