

Description

TYGRIS Bright Zinc Galve Spray is a quick drying, high performance zinc-rich bright protective coating used for the cosmetic finishing and protection of previously galvanized surfaces.

Formulated with a high purity powdered zinc metal (99%) and enriched with aluminium flake, TYGRIS Bright Zinc Galve Spray offers excellent adhesion and can be applied to both freshly cut metal or welded joints - helping prevent both oxidation and corrosion.

Outstanding Features

- Dried film contains in excess of 60% zinc by weight
- Highly flexible, quick drying – no secondary curing necessary
- Provides excellent adhesion to clean, prepared metal surfaces
- Excellent resistance to salt spray and weathering
- Suitable for welding through

Directions for Use

Ensure surface to be coated is clean, dry and free from grease. Shake can until agitator ball can be heard and then for a further 1 to 2 minutes. Spray from 25-30 cm, building up layers in light coats. Allow 10 minutes drying time.

Technical Data

Appearance	metallic Silver
Odour	Characteristic paint aroma
Contents	A solvent based solution of acrylic resin with micronized zinc and aluminium metal propelled by butane isobutane and propane
Flash Point	20°C
Solubility	insoluble in water
Temperature Range	-20°C to 100°C
Relative Density	
Flammability	Extremely Flammable
Health & Safety	Consult Safety Data Sheet available at tygrisindustrial.com
Storage	Store in a cool, dry place
Pack Size	500 ml Aerosols



1RH

KLMCHRBVV	<input type="checkbox"/>
RDDLIRBRKDMUBURU	<input type="checkbox"/>
BRLLRRIUBRV	<input type="checkbox"/>
BRKRMB	
LIRBRLOBRRLB	