

#### Description

Performance enhanced grease for high load applications. Used on chains and other moving metal parts, this high performance grease penetrates rapidly before thickening to tenacious grease which is highly resistant to throw off. The addition of extreme-pressure additives makes it particularly effective under heavy loads.

#### Benefits & Features

- Clear, non-staining
- Penetrates rapidly and thickens
- Highly resistant to throw-off
- Extreme-pressure additives for high loadings
- Use on chains and other moving parts

#### Directions for Use

Shake can well before use and spray from a distance of 15-30cm.

#### Technical Data

Appearance:	Yellow tinged liquid grease
Odour:	Oily
Contents:	Blend of mineral oil based grease, extreme-pressure additives and hydrocarbon propellants
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	-10°C to 80°C continuous, -10° to 150°C intermittent
Relative Density:	0.85
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at <a href="http://tygrisindustrial.com">tygrisindustrial.com</a> )
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols



#### Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.