

Description

TYGRIS HydroTough 100 is a safe and effective solution for tackling heavy fuel oils deposits, stubborn greases, bitumen, resins, waxes and aged oil contamination.

Tygris HydroTough 100 is recommended for use by local authorities, tar manufacturers, highway maintenance companies, industrial cleaners and bioremediation solution providers. Used for cleaning tools, equipment and machinery, HydroTough 100 is also effective in removing heavy deposits from concrete surfaces, tanks etc

Benefits & Features

- Totally safe to use and environmentally responsible
- Outlasts conventional cleaners/degreasers
- Acts as a bio-accelerator for complete breakdown of hydrocarbons
- Prevents grease and oil build up on machinery and equipment
- Extremely effective and economical in use
- Ideal for removing heavier contamination deposits
- Renders hydrocarbons non-flammable
- Aids biodegradation

Directions for Use

Can be used with pressure washers, steam cleaners, floor scrubbing machines or by hand.

Technical Data

| | |
|--------------------------|--|
| Appearance: | Yellow/Orange liquid |
| Odour: | Distinct |
| Contents: | |
| Flash Point: | >65°C Non-flammable |
| Solubility: | Miscible |
| Temperature Range: | |
| Relative Density (20°C): | 0.978 |
| Boiling Point: | 100°C |
| Freezing Point: | 0°C |
| Dilution Rates: | Effective use up to 100:1 General minimum use 10:1 |
| pH: | 5.0 +/- 0.5 |
| Viscosity: | |
| Flammability: | Non-Flammable |
| Health & Safety: | Consult Safety Data Sheet (availat tygrisindustrial.com) |
| Storage: | Store above 0°C |
| Pack Size: | 4 x 5ltr |

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

