PROTEAN

TECHNICAL DATA SHEET PROTEAN CHAIN & GEAR 150 TF7020

Description

PROTEAN Chain & Gear 150 is an NSF: H1 registered, fully synthetic oil designed for the effective lubrication of all types of conveyor and drive chains that require an ISO 150 oil within Food & Beverage, Packaging, Pharmaceutical and other cleanroom environments. Suitable for gearboxes and reduction units, PROTEAN Chain & Gear contains additives to extend servicing and lubrication intervals, boost performance, improved adhesion and offers excellent water wash-off resistance. Halal/Kosher Certified.

Benefits / features

Chains (Drive and Conveyor)

- · Penetrates to the links and pins reducing wear and extending chain life
- · Adhesive additives ensure no fling, thus providing lasting lubrication
- · Effective water resistance and corrosion prevention, even where alkali materials are present
- · Extremely wide temperature range ensures maximum application versatility

Gearboxes & Reduction Units

- · Extremely good oxidation stability which extends lubricant life
- Unaffected by water, demulsification ensures total separation of water from oil
- · Adhesive additives coat gears effectively and provide anti-wear protection at start-up
- · Synthetic oil with high Viscosity Index ensures reduced viscosity change with temperature increase

Directions for Use

For drive and conveyor chains: Apply sparingly by brush or oil can as required. It can also be applied automatically via a central drip-feed system.

For gear boxes or reduction units: Ensure that the manufacture's lubricant rating corresponds to <u>ISO 150 gear oil</u>. For optimum performance, drain gearbox of all previous lubricant.

Technical Data

Category:	H1 – Lubricants with incidental contact
NSF Registration No:	154240
Allergens:	Does not contain allergens, genetically
	modified ingredients, nut oil or derivatives.
Appearance:	Clear tacky oil
Base Oil:	Blend of synthetic oils
Viscosity:	149cSt @ 40°C, 17.7.7cSt @ 100°C
Viscosity Index:	136
Flash Point):	275°C
Solubility:	Insoluble in water
Operating Temperature Range:	-30°C to +200°C
Pack Sizes:	5 Ltr (TF7005) 20 Ltr (TF7020) 205 Ltr
	(TF7099) 1000 Ltr (TF7000)



The content of this data sheet is given in good faith but without warranty.

PROTEAN

31 Kyle Road, Irvine KA12 8LE Tel: +44 (0) 1294 311 066 technical@tygrisindustrial.com

Version 2 Pag<u>e 1 of 1</u>