

#### Description

A food grade, non-toxic oil developed for hydraulic systems in the food, drink, pharmaceutical and packaging equipment industries. Also for use in other applications where a clean, non-staining hydraulic oil is required.

#### Benefits & Features

- Low friction coefficient for excellent lubrication and wear reduction
- Fully synthetic to provide very wide temperature stability and extended service intervals
- Additives reduce foaming for less residue and scum build up

#### Directions for Use

For use in hydraulic systems where an ISO 46 viscosity grade is specified. Follow manufacturer's instructions and purge the system of the previous oil before re-filling. Does not contain allergens, genetically modified ingredients, nut oil or derivatives.

#### Technical Data

Category:	H1 – Lubricants with incidental contact
NSF Registration No:	162783
Allergens:	Does not contain allergens, genetically modified ingredients, nut oil or derivatives.
Appearance:	Does not contain allergens, genetically modified ingredients, nut oil or derivatives.
Base Oil:	Polyalphaolefin
Viscosity:	ISO grade 46
Relative Density:	0.85
Flash Point (COC):	>150°C
Solubility:	Insoluble in water
Operating Temperature Range:	-54° to 200°C
Pack Sizes:	5 Ltr (TF7405) 20 Ltr (TF7420) 205 Ltr (TF7499) 1000 Ltr (TF7400)



The content of this data sheet is given in good faith but without warranty.