

Description

A high quality water resistant grease for use in food processing environments where incidental food contact may occur. Used in applications where frequent washdown of equipment is essential. Suitable for use in bearings and sliding surfaces.

Benefits & Features

- High degree of water resistance
- Excellent corrosion protection
- Good anti wear and extreme pressure properties

Directions for Use

Apply with a grease gun, taking care not to over-lubricate.

Technical Data

| | |
|------------------------------------|--|
| Category: | H1 – Lubricants with incidental contact |
| NSF Registration No: | 148573 |
| Allergens: | Does not contain allergens, genetically modified ingredients, nut oil or derivatives |
| Appearance: | Smooth off white adhesive grease |
| NLGI Classification: | 2 |
| Thickener: | |
| Drop Point (IP132): | |
| Base Oil: | Technical white oil |
| Base Oil Viscosity: | |
| Solid lubricant: | PTFE |
| 4 Ball Weld Load (IP239): | 315kg |
| - Scar Diameter @ 40Kg for 1 hour: | 0.6mm |
| Copper Corrosion (IP112): | 1b |
| Water washout (ASTM D1264) @38°C: | >2.5% @ 38°C |
| Dynamic Corrosion Resistance: | 0:0 |
| Relative Density: | |
| Melting Point: | >150°C |
| Solubility: | Insoluble in water |
| Operating Temperature Range: | -25° to 110°C |
| Pack Sizes: | 12 x 400g Cartridges |



The content of this data sheet is given in good faith but without warranty.

