

Description

A specially developed multi-purpose lithium complex grease for lubricating all anti-friction and plain bearings for use in industrial and automotive applications. The grease has shown exceptional performance providing extended lubrication intervals over a wide operating temperature range.

Benefits & Features

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- Highly versatile multi purpose grease
- Good mechanical stability extends lubrication intervals

Directions for Use

Apply by grease gun, manually or by centralised pumping system capable of conveying NLGI 2 greases.

Technical Data

Appearance:	Smooth blue grease
Base Oil:	Solvent refined mineral oil
NLGI Classification:	2
Thickener:	Lithium complex
Base Oil Viscosity:	150cSt minimum
Worked Penetration:	265 to 295
Water Washout:	3% @ 38°C, 4% @ 79°C
Four Ball Weld Load:	450kg
Wear Load Index:	62
Timken OK Load:	20kg
Oil Separation:	5% maximum
Temperature range:	-20 to 150°C
Drop Point:	250°C minimum
Copper Corrosion:	Pass
Resistance to Corrosion (Emcor):	0:0
Pack Sizes:	12 x 400gm

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

